



## Material Data Sheet Revised 8/01/18

Product:	Flashing Tape
Base Material:	Spun Bonded Woven Coated Polyester Fabric
Color:	Black, tan, more available upon request.
Product Dimensions:	Widths: 4" and 6" / Lengths: 75' and 100' per roll

### Description

Self-adhered synthetic, woven coated membrane with a film release liner. Able to stick in both low and high temperatures. Able to withstand UV exposure for up to 6 months. The tape is adhered to a split liner for easy and accurate positioning and installation.

### Technical Specifications

Properties	Value	Unit
Tape Thickness	11	Mil.
Adhesion to Steel	3500-4000	g/inch
Anchorage	Pass	
Service Temperature	-10°C - 80°C	

The information presented in this data sheet is believed to be accurate and is not intended to constitute a specification. The values given reflect average measurements, which can vary slightly. Users are encouraged to determine the suitability of this product for their own particular application(s).

Base on terms and conditions  
 Seller's only obligation shall be to replace such quantity of the product proven to be defective. Seller shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use, or inability to use the product for his/her use, and the user assumes all risk and liability whatsoever in connection therewith. The foregoing may not be changed, except by an agreement signed by an officer or seller. We hereby certify that goods covered by this quotation have been produced in compliance with the Fair Labor Standards Act of 1983, as amended. Any credit memos to purchaser shall expire if not used within one year from date of credit memo.